

Declaration of Performance

nr. DOP – 3 – FIBATAPE – 01

1.	Unique identification code of the product-type:	P – 3 – FIBATAPE
2.	Product:	FibaTape®
3.	Intended use of construction product:	Glass fibre joint tape for gypsum plasterboards
4.	Manufacturer:	SAINT-GOBAIN ADFORS CZ, s.r.o. Sokolovská 106 570 01 Litomyšl Czech Republic
5.	System of assessment:	System 3
6.	European Assessment Document: European Technical Assessment: Technical Assessment Body:	EAD 070002-00-0505: 2016 ETA-09/0075 of 02.07.2018 TECHNICKÝ A ZKUŠEBNÍ ÚSTAV STAVEBNÍ PRAHA, s.p.

Declared performance:

Essential characteristics	Performance
Reaction to fire	NPD
Tensile strength (standard conditions 23± 1°C)	$\sigma_k = 15$ N/mm
Resistant to dampness	$\sigma_k = 9$ N/mm 37%
Self-Adhesion ability (low and high temperature)	no visual changes and other defects
Jointing material penetration ability	57 N

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

In Litomyšl, date 02.07.2018



.....
Erik Pellati, Product Manager

CE mark:

	
09	
CZ00012661	
Identification code: P – 3 – FIBATAPE	
Ref. nr. of DoP: DOP – 3 – FIBATAPE – 01	
FibaTape®	
Glass fibre joint tape for gypsum plasterboards	
Essential characteristics	Performance
Tensile strenght (standard conditions 23± 1°C)	$\sigma_k = 15 \text{ N/mm}$
Resistant to dampness	$\sigma_k = 9 \text{ N/mm}$ 37%
Self-Adhesion ability	no visual changes and other defects
Jointing material penetration ability	57 N
European Assessment Document:	EAD 070002-00-0505
European Technical Assessment:	ETA-09/0075