




Attaches like metal lath and meets IBC and IRC building code requirements







Why should you make the switch to FibaLath?

- Lightweight and pliable, easier and safer to cut, lift and carry than metal lath
- Self-furring, three dimensional profile is attached same way as metal lath
- Meets International Building Code® (IBC) and International Residential Code® (IRC) requirements (Intertek Code Compliance Research Report CCRR-0249)



ADFORS FibaLath® is an innovative fiberglass lath designed for use in stucco applications and exterior or interior walls of manufactured stone and brick facades. The three dimensional profile of FibaLath is self-furring and is attached the same way as metal lath.

Additional Features & Benefits include:

- Alkali-resistant for long term performance. Will not rust or rot.
- Non-directional which means it can be applied vertically or horizontally
- Over 6 times lighter weight than metal lath (per unit area)

PART #	ROLL SIZE WIDTH X LENGTH	ROLL AREA (FT²)	ROLL UPC	CASE UPC	CASE COUNT
FLX7207-A	39 in x 25 ft	81	038662946176	10038662946173	6
FLX7206-A	39 in x 55 ft	180	038662946169	10038662946166	4
FLX7205-A	39 in x 150 ft	491	038662946152	N/A	1

METAL SHEET			FIBALATH		WEIGHT	
SQUARE YARDS	# SHEETS	WEIGHT (2.5#)	ROLL SIZE	WEIGHT	SAVINGS	
54.7	27	136.27 lb	150 ft	30 lb	78%	
20	10	50 lb	55 ft	11 lb	78%	
9	4	22.75 lb	25 ft	5 lb	80%	

FibaLath is a trademark of Saint-Gobain ADFORS America, Inc.

U.S. Patent 7,625,827 and 7,902,092.



Saint-Gobain ADFORS

140 John James Audubon Pkwy Suite 102 Amherst, NY 14228 - USA

Phone: 800-762-6694

1919 6/22